

4PX266A

User's Manual Version 1.0

The information presented in this publication has been made carefully for reliability; however, no responsibility is assumed for inaccuracies. Specifications are subject to change without notice.

IBM, PC/AT, and PC/XT are trademarks of International Business Machines Corporation.
Socket478 is a trademark of Intel Corporation
AWARD is a registered trademark of Phoenix Software Inc.
MS-DOS and WINDOWS NT are registered trademarks of Microsoft Corporation.

Trademarks and/or registered trademarks are the properties of their respective owners.

Table of Contents

Introduction

1. Motherboard Description

1.1 Features	
1.1.1 Hardware	1-2
1.1.2 Software	1-4
1.1.3 Attachments	1-4
1.2 Motherboard Installation	
1.2.1 Motherboard Map	1-5
1.2.2 Motherboard Layout	1-6
1.3 Motherboard Connectors	
1.3.1 Front Panel Connector(PANEL)	1-8
1.3.2 Floppy Disk Connector(FDD)	1-9
1.3.3 Hard Disk Connectors(IDE1/IDE2)	1-9
1.3.4 ATX 4-pin & 20-pin/AUX Power Connector(ATX/CN3/AUX)	1-10
1.3.5 Infrared Connector	1-10
1.4 Back Panel Connectors	
1.4.1 PS/2 Mouse/Keyboard CONN.	1-11
1.4.2 USB Connectors(USB1 & USB2 & USB3)	1-11
1.4.3 RJ-45 Connector	1-12
1.5 Serial and Parallel Interface ports	1-13
1.6 CPU Installation	
1.6.1 CPU Installation Procedure(Socket 478)	1-15
1.6.2 CPU Clock Frequency Setting(J4)	1-16
1.7 Jumper Setting	
1.7.1 CPU/Fan Connectors(FAN1/2/3)	1-17
1.7.2 Wake-On-Modem Header(WOM)	1-18
1.7.3 Wake-On-LAN Header(WOL)	1-18
1.7.4 AC'97 Codec Selection(J3)	1-18
1.7.5 CMOS Function Setting(JBAT)	1-19
1.7.6 IrDA Connector(IR)	1-19
1.8 DDR SDRAM Installation	
1.8.1 DDR	1-20
1.8.2 How to install a DDR Module	1-20

Table of Contents

1.9 Audio Subsystem	
1.9.1 CD-Audio-IN Connector(CDIN1/CDIN2)	1-21
1.9.2 Telephone in Connector(TAD)	1-22
1.10 Smart Panel Onboard Connector	
1.10.1 Port 80 Debug Function(SP-J6)	1-23
1.10.2 Second BIOS Connector(SP-J2)	1-23
1.10.3 AUX LINE Connector(SP-J5)	1-23
1.10.4 Front COM2 Header Connector(SP-J7)	1-24
1.10.5 Front USB3,4 Header Connector(SP-J8)	1-24

2. BIOS Setup

2.1 Main Menu	2-4
2.2 Standard CMOS Features	2-7
2.3 Advanced BIOS Features	2-10
2.4 Advanced Chipset Features	2-14
2.5 Integrated Peripherals	2-19
2.6 Power Management Setup	2-25
2.7 PnP/PCI Configurations	2-30
2.8 PC Health Status	2-34
2.9 Frequency/Voltage Control	2-36
2.10 Load Fail-Safe Defaults	2-37
2.11 Load Optimized Defaults	2-38
2.12 Set Supervisor/user Password	2-39
2.13 Save & Exit Setup	2-41
2.14 Exit Without Saving	2-42

3. Driver Installation

3.1 Main Menu	3-1
3.2 Installing VIA 4 in 1 Driver	3-2
3.3 Installing Audio Driver	3-3
3.4 Installing LAN Driver	3-4

a. Appendix

Introduction

System Overview

This manual was written to help you start using this product as quickly and smoothly as possible. Inside, you will find the answers to solve most of the problems. In order for this reference material to be of greatest use, refer to the “expanded table of contents” to find relevant topics.

This board provides a total PC solution by incorporating the System , I/O , and PCI IDE. The mainboard support single Intel P4 processors base PC ATX system, PCI Local Bus, ACR Bus, and AGP Bus to upgrades your system performance.

It is ideal for multi-tasking and fully supports MS-DOS, Windows, Windows NT , Windows ME, Windows 2000, Novell, OS/2, Windows95/98, Windows 98SE, Windows XP, UNIX, SCO UNIX etc.

This manual also explains how to install the mainboard for operation, and how to setup your CMOS configuration with the BIOS setup program.

1. Motherboard Description

1.1 Features

1.1.1 Hardware

CPU

- 400MHz System Interface speed.
- Single Socket 478 for Intel P4™ up to 2GHz or higher(Northwood Processor).
- Support Intel Netburst™ Micro-architecture.

DDR SDRAM Memory

- Supports 64/128/256....MB DDR module socket.
- Supports Synchronous DDR SDRAM(2.5V).
- Supports a maximum memory size of 3GB with DDR SDRAM.

AGP Speed

- Supports 1X/2X/4X AGP Bus.
- Only support AGP 66 MHz/1.5V for 4X device.

Chipset

- VIA VT8753 North Bridge. (P4X266)
- VIA VT8233 South Bridge.

Bus Slots

- Provide one ACR slot for ISA side and AGP slot.
- Five 32-bit PCI bus.

Universal Serial Bus

- Supports two back Universal Serial Bus(USB)Ports and four front Universal serial Bus(USB)Ports.

BIOS

- The mainboard BIOS provides “Plug & Play” BIOS which detects the peripheral devices and expansion cards of the board automatically.
- The mainboard provides a Desktop Management Interface (DMI) function which records your mainboard specifications.
- BIOS support CD-ROM, SCSI, LAN BOOT, Temperature sensor, LAN, Modem, Alarm Bus CLK setup with BIOS.

Hardware Monitor Function

- CPU Fan Speed Monitor.
- CPU Temperature Monitor.
- System Voltage Monitor.

Flash Memory

- Support 2MB flash memory.
- Support ESCD Function.

IDE Built-in On Board

- Supports four IDE devices.
- Supports PIO Mode 5, Master Mode, high performance hard disk drives.
- Support Ultra DMA 33/66/100 Bus Master Mode.
- Supports IDE interface with CD-ROM.
- Supports high capacity hard disk drives.
- Support LBA mode.

PCI-Based AC 97 Digital Audio Processor

- AC 97 2.1 interface.
- 16 channels of high-quality sample rate conversion.
- 16x8 channel digital mixer.
- Stereo 10 band graphic equalizer.
- Sound Blaster and Sound Blaster Pro emulation.

Network

- Support 10/100Mb/s operation.
- Support wake on LAN function and remote wake up.

WOL & WOM (Wake On LAN & Wake On Modem)

Supports system power up from LAN & Modem ring up .

Smart Panel

Supports BIOS Port 80H POST Code output to debug LED.

I/O Built-in On Board

- Supports one multi-mode Parallel Port.
 - (1)Standard & Bidirection Parallel Port
 - (2)Enhanced Parallel Port (EPP)
 - (3)Extended Capabilities Port
- Supports two serial ports, 16550 UART.
- Supports one Infrared transmission (IR).
- Supports PS/2 mouse and PS/2 Keyboard.
- Supports ATX 4 pin power connector +12V in.
- Supports AUX 6 pin power connector.
- Supports 360KB, 720KB, 1.2MB, 1.44MB, and 2.88MB floppy disk drivers.

1.1.2 Software

BIOS

- AWARD legal BIOS.
- Supports APM 1.2.
- Supports USB Function.
- Supports ACPI

Operation System


- Supporting the highest performance for MS-DOS, Windows, Windows NT, Windows 2000, Windows ME, Novell, OS/2, Windows 95/98, Windows 98 SE, Windows XP, UNIX, SCO UNIX etc.

1.1.3 Attachments


- HDD UDMA66/100 Cable.
- FDD Cable.
- Flash Memory Written for BIOS Update.
- USB2 Cable (**Option**).
- Fully Setup CD Driver built in Utility(Ghost, Anitivirus, Adobe Acrobat).
- This Manual.

1.2 Motherboard Installation


1.2.1 Motherboard Map



1.2.2 Motherboard Layout




1.3 Motherboard Connectors



- | | |
|----------------------------------|--|
| 1.Back Panel I/O Connectors | 2.CD Audio-In Connector |
| 3.Wake-On-LAN Connector | 4.Wake-On-Modem Connector |
| 5.Front COM2 Connector | 6.Front USB2/USB3 Connector |
| 7.Front Panel Connector | 8.Fan Connectors(Fan1/2/3) |
| 9.IDE Connectors | 10.Floppy Connector |
| 11.ATX Power Connector(ATX/CN3) | 12.AUX Power Connector |
| 13.IR Connector | 14.CPU Clock Freq. Setting(J4) |
| 15.AC'97 CODEC Selection(J3) | 16.Telephone in Connector(TAD) |
| 17.CMOS Function Selection(JBAT) | 18.Smart Panel Function(SP-J2/SP-J6/SP-J5)(option) |

1.3.1 Front Panel Connector (PANEL)



ATX Power Switch (PW_BN)

The system power is controlled by a momentary switch connected to this lead. Pushing the button once will switch the system ON. The system power LED lights when the system's power is on .

Power LED Lead (PW_LED)

The system power LED lights when the system power is on.

Speaker Connector (SPEAKER)

An offboard speaker can be installed onto the motherboard as a manufacturing option. An offboard speaker can be connected to the motherboard at the front pannel connector. The speaker (onboard or offboard) provides error beep code information during the Power Self-Test when the computer cannot use the video interface. The speaker is not connected to the audio subsystem and does not receive output from the audio subsystem.

Hard Drive LED Connector (HD_LED)

This connector supplies power to the cabinet IDE activity LED. Read and write activity by devices connected to the Primary or Secondary IDE connectors will cause the LED to light up.

S3_LED Lead (S3_LED)

The system S3_LED lights when the system suspend is on the S3 modle.

Reset Switch Lead (RESET)

The connector can be connected to a momentary SPST type switch that is normally open. When the switch is closed, the motherboard resets and runs the POST.

SMI Suspend Switch Lead (EXTSMI)

This allows the user to manually place the system into a suspend mode of Green mode. System activity will be instantly decreased to save electricity and expand the life of certain components when the system is not in use. This 2-pin connector (see the figure) connects to the case-mounted suspend switch. If you do not have a switch for the connector, you may use the "Turbo Switch" instead since it does not have a function. SMI is activated when it detects a short. It may require one or two pushes depending on the position of the switch. Wake-up can be controlled by settings in the BIOS but the keyboard will always allow wake-up (the SMI Suspend Switch Lead cannot wake-up the system). If you want to use this connector, the "Suspend Switch" in the Power Management Setup of the BIOS SOFTWARE section should be on the default setting of Enable.

1.3.2 Floppy Disk Connector (FDD)

This connector supports the provided floppy drive ribbon cable. After connecting the single end to the board, connect the two plugs on the other end to the floppy drives.

1.3.3 Hard Disk Connectors (IDE1/IDE2)

These connectors support the provided IDE hard disk ribbon cable. After connecting the single end to the board, connect the two plugs at the other end to your hard disk.

If you install two hard disks, you must configure the second drive to Slave mode by setting its jumper settings. BIOS now supports SCSI device or IDE CD-ROM boot up (see "HDD Sequence SCSI/IDE First" & "Boot Sequence" in the BIOS Features Setup of the BIOS SOFTWARE) (Pin 20 is removed to prevent inserting in the wrong orientation when using ribbon cables with pin 20 plugged) .

1.3.4 ATX 4-pin/ATX 20-pin/AUX 6-pin Power Connector (CN3/ATX/AUX)

- This connector supports the power button on-board. Using the ATX power supply, functions such as Modem Ring Wake-Up and Soft Power Off are supported on this motherboard . This power connector supports instant power-on functionality, which means that the system will boot up instantly when the power connector is inserted on the board.
- ATX 4-pin power connector only support +12V voltage.

Pin CN3 Signal		Pin CN3 Signal	
1	GND	2	GND
3	+12V	4	+12V


Pin ATX Signal		Pin ATX Signal	
1	3.3V	11	3.3V
2	3.3V	12	-12V
3	GND	13	GND
4	5V	14	PS-ON
5	GND	15	GND
6	5V	16	GND
7	GND	17	GND
8	PW-OK	18	NC
9	5V_SB	19	5V
10	12V	20	5V

Pin AUX Signal		Pin AUX Signal	
1	GND	4	+3.3V
2	GND	5	+3.3V
3	GND	6	+5V

1.3.5 Infrared Connector (IR)

After the IrDA interface is configured, files can be transferred from or to portable devices such as laptops, PDAs, and printers using application software.

1.4 Back Panel Connectors




1.4.1 PS/2 Mouse /Keyboard CONN.

The motherboard provides a standard PS/2 mouse / Keyboard mini DIN connector for attaching a PS/2 mouse. You can plug a PS/2 mouse / Keyboard directly into this connector.

1.4.2 USB Connectors: USB1+RJ-45 (RJ-45 port option)

The motherboard provides a OHCI(Open Host Controller Interface)Universal Serial Bus Roots for attaching USB devices such as a keyboard, mouse and other USB devices. You can plug the USB devices directly into this connector.

RJ-45




1 2 3 4
USB1

RJ-45	10/100M LAN Port
Pin	Signal
1	+5V_SB
2	USBP0-(USBP1-)
3	USBP0+(USBP1+)
4	GND

NOTE:


If the mainboard don't have LAN function, there will be no RJ-45 port on board.

Front Two USB Connectors: USB2 & USB3



USB2

USB3



1.4.3 RJ-45 Connector

Onboard 10/100Mb PCI Fast Ethernet Network.
 The RJ-45 connector is located on top of the USB connectors.
 The connector allows the motherboard to connect to a Local Area Network (LAN) through a network hub .

1.5 Serial and Parallel Interface Ports

This system comes equipped with two serial ports and one parallel port. Both types of interface ports will be explained in this chapter.

The Serial Interfaces: COM1/COM2

The serial interface port is sometimes referred to as an RS-232 port or an asynchronous communication port. Mice, printers, modems and other peripheral devices can be connected to a serial port. The serial port can also be used to connect your computer system. If you wish to transfer the contents of your hard disk to another system it can be accomplished by using each machine's serial port.

COM1/COM2




COM2




The serial port on this system has one 9-pin connector. Some older computer systems and peripherals used to be equipped with only a 25-pin connector. If you need to connect your 9-pin serial port to an older 25-pin serial port, you can purchase a 9-to-25 pin adapter.

Signal	DB9 Pin	DB25 Pin
DCD	1	8
RX	2	3
TX	3	2
DTR	4	20
GND	5	7
DSR	6	6
RTS	7	4
CTS	8	5
RI	9	22



Parallel Interface Port


Unlike serial ports, parallel interface ports have been standardized and should not present any difficulty interfacing peripherals to your system. Sometimes called a Centronics port, the parallel port is almost exclusively used with printers. The parallel port on your system has a 25-pin, DB 25 connector(see the picture below).



1.6 CPU Installation


1.6.1 CPU Installation Procedure: Socket 478

1. Pull the lever sideways away from the socket then raise the lever to a 90-degree angle.
2. Locate Pin 1 in the socket and look for the white dot or cut edge in the CPU. Match Pin 1 with the white dot/cut edge then insert the CPU.
3. Press the lever down to complete the installation.
4. Make sure the spec of the heatsink is good enough.



1.6.2 CPU Clock Frequency Setting: J4

Overclocking is operating a CPU/Processor beyond its specified frequency. J4 jumper is used for the CPU Front Side Bus Frequencies from 66MHz to 133MHz.




1-2	3-4	5-6	7-8	CPU(MHz)	PCI(MHz)
ON	ON	OFF	OFF	66	33.3
OFF	ON	OFF	OFF	100	33.3
OFF	OFF	OFF	OFF	133	33.3

NOTE:

Intel CPU doesn't support overclock and overcore, we don't recommend users use these funtions for possible CPU damage.

1.7 Jumper Setting

A jumper has two or more pins that can be covered by a plastic jumper cap, allowing you to select different system options.



1.7.1 CPU/System Fan Connector: Fan1

Pin	Assignment
1	FAN1
2	+12VDC
3	Ground

1.7.1 CPU/System Fan Connector: Fan2

Pin	Assignment
 1	FAN2
2	+12VDC
3	Ground

1.7.1 CPU/System Fan Connector: Fan3

Pin	Assignment
 1	NC
2	+12VDC
3	Ground

1.7.2 Wake-On Modem Header: WOM

Pin	Assignment
 1	5V_SB
2	Ground
3	Signal

1.7.3 Wake-On LAN Header: WOL

Pin	Assignment
 1	5V_SB
2	Ground
3	Signal

1.7.4 AC'97 CODEC Selection: J3

Pin	Assignment
1-2	On board CODEC is used (Default)
2-3	ACR Slot is used (for ISA side)

1.7.5 CMOS Function Selection: JBAT

Pin	Assignment
1-2	Normal (Default)
2-3	Clear CMOS

NOTE:

(Please follow the procedure below to clear CMOS data.)

- (1) Remove the AC power line.
- (2) JBAT(2-3) Closed.
- (3) Wait five seconds.
- (4) JBAT(1-2) Closed.
- (5) AC Power on.
- (6) Reset your desired password or clear CMOS data.

1.7.6 IrDA Connector: IR

Pin	Assignment	Pin	Assignment
1	+5V	2	
3		4	CIRRX
5	IRRX1	6	5VSB
7	GND	8	
9	IRTX	10	

1.8 DDR SDRAM Installation

1.8.1 DDR


DDR SDRAM Access Time: 2.5V Unbuffered PC1600/
PC2100 Type required.

DDR SDRAM Type: 64MB, 128MB, 256MB, 512MB, 1GB
DDR Module. (184 pin)


Bank	Memory module
DDR 1 (Bank 0-1)	64MB, 128MB, 256MB, 512MB, 1GB 184 pin, 2.5V DDR SDRAM
DDR 2 (Bank 2-3)	64MB, 128MB, 256MB, 512MB, 1GB 184 pin , 2.5V DDR SDRAM
DDR 3 (Bank 4-5)	64MB, 128MB, 256MB, 512MB, 1GB 184 pin, 2.5V DDR SDRAM
	Total System Memory (Max 3GB)

1.8.2 How to install a DDR Module

1. The DDR socket has a “Plastic Safety Tab” and the DDR memory module has an asymmetrical notch”, so the DDR memory module can only fit into the slot in one direction.
2. Push the tabs out. Insert the DDR memory modules into the socket at a 90-degree angle then push down vertically so that it will fit into place.
3. The Mounting Holes and plastic tabs should fit over the edge and hold the DDR memory modules in place.



1.9 Audio Subsystem



1.9.1 CD Audio-in Connectors: CDIN1/CDIN2


Pin CDIN1	Assignment
1	CD-L
2	GND
3	GND
4	CD-R

Pin CDIN2	Assignment
1	GND
2	CD-L
3	GND
4	CD-R

1.9.2 Telephone in Connector: TAD

Pin TAD	Assignment
1	PHONE
2	GND
3	GND
4	MONO_OUT

1.10 Smart Panel Onboard Connector



Note:
 The motherboard provides the pin leads for Smart Panel. If you want POST Error Code or Smart Panel function, please refer to Smart Panel (SPPX266A) manual.

1.10.1 Port 80 Debug Function: SP-J6

For Smart Panel connector(SP-J6) to M/B (SP-J6).

Pin SP-J6	Assignment	Pin SP-J6	Assignment
1	ERD4	2	ERD0
3	ERD5	4	ERD1
5	ERD6	6	ERD2
7	ERD7	8	ERD3
9	GND	10	NC

1.10.2 Second BIOS Connector: SP-J2

For Smart Panel connector(SP-J2) to M/B (SP-J2).

Pin BIOS	Assignment	Pin BIOS	Assignment
1	XDD0	2	+5V
3	XDD1	4	XAA0
5	XDD2	6	XAA1
7	XDD3	8	XAA2
9	XDD4	10	XAA3
11	XDD5	12	XAA4
13	XDD6	14	XAA5
15	XDD7	16	XAA6
17	NC	18	DISABLE
19	ROMCS-	20	XAA7
21	MEMR-	22	XAA8
23	MEMW-	24	XAA9
25	SA18J	26	XAA10
27	XAA17	28	XAA11
29	XAA16	30	XAA12
31	XAA15	32	XAA13
33	NC	34	XAA14

1.10.3 AUX Line Connector: SP-J5

For Smart Panel connector(SP-J5) to M/B (SP-J5).

Pin SP-J5	Assignment	Pin SP-J5	Assignment
1	LINE_OUT_L	2	LINE_OUT_R
3	LINE_IN_L	4	LINE_IN_R
5	MIC_IN_L	6	NC

1.10.4 Front COM2 Header Conn.: SP-J7(COM2)

For Smart Panel connector(SP-J7) to M/B
(SP-J7).

Pin SP-J7	Assignment	Pin SP-J7	Assignment
1	DCD	2	RX
3	TX	4	DTR
5	GND	6	DSR
7	RTS	8	CTS
9	RI		

1.10.5 Front USB3,4 Header Conn.: SP-J8(USB3)

For Smart Panel connector(SP-J8) to M/B
(USB3).

Pin SP-J8	Assignment	Pin SP-J8	Assignment
1	VCC	2	GND
3	P4-	4	GND
5	P4+	6	P5+
7	GND	8	P5-
9	GND	10	VCC

2. BIOS Setup

Introduction

This manual discussed the Award Setup program built into the ROM BIOS. The Setup program allows the user to modify the basic system configuration. This special information is then stored in battery-backed RAM so that it retains the setup information when the power is turned off.

The Award BIOS installed in your computer system's ROM (Read Only Memory) is a custom version of an industry standard BIOS. This means that it supports Intel P4 processors input/output system. The BIOS provides critical low-level support for standard devices such as disk drives and serial and parallel ports.

The rest of this manual is intended to guide you through the process of configuring your system using Setup.

Plug and Play Support

This AWARD BIOS supports the Plug and Play Version 1.0A specification. ESCD(Extended System Configuration Data)write is supported.

EPA Green PC Support

This AWARD BIOS supports Version 1.03 of the EPA Green PC specification.

APM Support

This AWARD BIOS supports Version 1.1&1.2 of the Advanced Power Management(APM) specification. Power management features are implemented via the System Management Interrupt(SMI). Sleep and Suspend power management modes are supported. Power to the hard disk drives and video monitors can be managed by this AWARD BIOS.

PCI Bus Support

This AWARD BIOS also supports Version 2.1 of the Intel PCI (Peripheral Component Interconnect) local bus specification.

Support CPU

This AWARD BIOS supports the Intel P4 CPU processor.

Using Setup

In general, you use the arrow keys to highlight items, press <Enter> to select, use the <PgUp> and <PgDn> keys to change entries, press <F1> for help and press <Esc> to quit. The following table provides more detail about how to navigate in the Setup program by using the keyboard.

Note:

(BIOS version 1.0 is for reference only. If there is a change in BIOS version, please use the actual version on the BIOS.)

Keystroke	Function
Up arrow	Move to previous item
Down arrow	Move to next item
Left arrow	Move to the item on the left(menu bar)
Right arrow	Move to the item on the right(menu bar)
Esc	Main Menu: Quit without saving changes Submenus: Exit Current page to the next higher level menu
Move Enter	Move to item you desired
PgUp key	Increase the numeric value or make changes
PgDn key	Decrease the numeric value or make changes
+Key	Increase the numeric value or make changes
-Key	Decrease the numeric value or make changes
Esc Key	Main menu-Quit and not save changes into CMOS Status Page Setup Menu and option Page Setup Menu-Exit Current page and return to Main Menu
F1 Key	General help on Setup navigation keys.
F5 Key	Load previous values from CMOS
F6 Key	Load the fail-safe defaults from BIOS default table
F7 Key	Load the optimized defaults
F10 Key	Save all the CMOS changes and exit

2.1 Main Menu

Once you enter AWARD BIOS CMOS Setup Utility, the Main Menu will appear on the screen. The Main Menu allows you to select from several setup function. Use the arrow keys to select among the items and press<Enter> to accept and enter the sub-menu.

“WARNING”

The information about BIOS defaults on manual (Figure 1,2,3,4,5,6,7,8,9,10,11,12,13,14)is just for reference, please refer to the BIOS installed on the board for updated information.

© Figure 1. Main Menu

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

Standard CMOS Features	Frequency/Voltage Control
Advanced BIOS Features	Load Fail-Safe Defaults
Advanced Chipset Features	Load Optimized Defaults
Integrated Peripherals	Set Supervisor Password
Power Management Setup	Set User Password
PNP/PCI Configurations	Save & Exit Setup
PC Health Status	Exit Without Saving
Esc : Quit F9 : Menu in BIOS ←→↑↓: Select Item	
F10 : Save & Exit Setup	
Time , Date , Hard Disk Type ...	

Standard CMOS Features

This setup page includes all the items in standard compatible BIOS.

Advanced BIOS Features

This setup page includes all the items of the BIOS special enhanced features.

Advanced Chipset Features

This setup page includes all the items of the Chipset special enhanced features.

Integrated Peripherals

This selection page includes all the items of the IDE hard drive and Programmed Input/Output features.

Power Management Setup

This setup page includes all the items of the power management features.

PnP/PCI Configurations

This setup page includes the user defined or default IRQ Setting.

PC Health Status

This page shows the hardware Monitor information of the system.

Frequency / Voltage Control

This setup page controls the CPU's clock and frequency ratio.

Load Fail-Safe Defaults

Use this menu to load the BIOS default values for the minimal/stable performance for your system to operate.

Load Optimized Defaults

These settings are more likely to configure a workable computer when something is wrong. If you cannot boot the computer successfully, select the BIOS Setup options and try to diagnose the problem after the computer boots. These settings do not provide optional performance.

Set Supervisor Password

Change, set, or, disable password. It allows you to limit access to the system and Setup, or just to Setup.

Set User Password

You can specify both a User and a Supervisor password. When you select either password option, you are prompted for a 1-6 character password. Enter the password and then retype the password when prompted.

Save & Exit Setup

Save CMOS value changes to CMOS and exit setup.

Exit Without Saving

Abandon all CMOS value changes and exit setup.

2.2 Standard CMOS Features

This item in the Standard CMOS Setup Menu is divided into 10 categories. Each category includes no, one or more than one setup items. Use the arrow keys to highlight the item and then use the <PgUp> or <PgDn> keys to select the value you want in each item.

© Figure 2. Standard CMOS Features

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

Standard CMOS Features

Date(mm:dd:yy)	Tue,Jun 6 2000	Item Help
Time (hh:mm:ss)	11:26:10	
IDE Primary Master	None	Menu Level
IDE Primary Slave		Change the day, month,year and century.
IDE Secondary Master		
IDE Secondary Master	None	
IDE Secondary Master		
Drive A	1.44M,3.5 in	
Drive B	None	
Video	EGA/VGA	
Halt On	All,But Keyboard	
Base Memory	640K	
Extended Memory	65472K	
Total	1024K	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

Main Menu Selections

This table shows the selections that you can make on the Main Menu.

Item	Options	Description
Date	Month DD YYYY	Set the system,date. Note that the 'Day' automatically changes when you set the data.
IDE Primary Master	Options are in its sub menu.	Press<Enter> to enter the sub menu of detailed.
IDE Primary Slave	Options are in its sub menu.	Press<Enter> to enter the sub menu of detailed.
IDE Secondary Master	Options are in its sub menu.	Press<Enter> to enter the sub menu of detailed.
IDE Secondary Slave	Options are in its sub menu.	Press<Enter> to enter the sub menu of detailed.
Drive A Drive B	None 360K, 5.25in 1.2M, 5.25in 720K, 3.5in 1.44M, 3.5in 2.88M, 3.5in	Select the type of floppy disk drive installed in your system.
Video	EGA/VGA CGA 40 CGA 80 MONO	Select the default video device.

Item	Options	Description
Halt On	All Errors No Errors All, but Keyboard All, but Diskette All, but Disk/Key	Select the situation in which you want the BIOS to stop the POST process and notify.
Base Memory	N/A	Displays the amount of conventional memory detected during boot up.
Extended Memory	N/A	Displays the amount of conventional memory detected during boot up.
Total Memory	N/A	Displays the total memory available in the system.

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software
IDE Primary Master

IDE HDD Auto-Detection	Press Enter	Item Help
IDE Primary Master	Auto	Menu Level
Access Mode	Auto	
Capacity	13022MB	
Cylinder	25232	
Head	16	
Precomp	0	
Landing Zone	25231	
Sector	61	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

2.3 Advanced BIOS Features

© Figure 3. Advanced BIOS Features

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

Advanced BIOS Features

Virus Warning	Disabled	Item Help
CPU L1 & L2 Cache	Enabled	Menu Level
CPU L2 Cache ECC Checking	Enabled	
Quick Power On Self Test	Enabled	Allows you to choose the VIRUS warning feature for IDE Hard Disk boot sector protection. If this function is enabled and someone attempts to write data into this area, BIOS will show a warning message on screen and alarm beep
First Boot Device	Floppy	
Second Boot Device	HDD-0	
Third Boot Device	LS120	
Boot Other Device	Enabled	
Swap Floppy Drive	Disabled	
Boot Up Floppy Seek	Enabled	
Boot Up NumLock Status	On	
Typematic Rate Setting	Disabled	
Typematic Rate (Chars/Sec)	6	
Typematic Delay (Msec)	250	
Security Option	Setup	
OS Select For DRAM	Non-OS2	
Video BIOS Shadow	Enabled	
Small Logo(EPA) Show	Disabled	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

Virus Warning

This option allows you to choose the VIRUS Warning feature for IDE Hard Disk boot sector protection. If this function is enabled and someone attempts to write data into this area, BIOS will show a warning message on screen and alarm beep.

The Choices: Disabled(default), Enabled.

CPU L1 & L2 Cache

This fields allow you to Enable or Disable the CPU'S "Level 1" & "Level 2" cache. Caching allows better performance.

Enabled (default) Enabled cache.

Disabled Disabled cache.

CPU L2 Cache ECC Checking

The item allows you to enable/disable CPU L2 Cache ECC Checking.

The Choices: Enabled(default), Disabled.

Quick Power On Self Test

This category speeds up Power on Self-Test(POST) after you power up the computer. If it is set to Enable, BIOS will shorten or skip some check items during POST.

Enabled (default) Enabled quick POST.

Disabled Normal POST.

First/Secondary/Third Boot Device

This BIOS attempts to load the operating system from the devices in the sequence selected in these items.

The Choices: Floppy, LS120, HDD-0, SCSI, CDROM, HDD-1, HDD-2, HDD-3, ZIP100, USB-FDD, USB-ZIP, USB-CDROM, USB-HDD, LAN, Disabled.

Boot Other Device

The Choices: Enabled(default), Disabled.

Swap Floppy Drive

If the system has two floppy drives, you can swap the logical drive name assignments.

The Choices: Disabled(default), Enabled.

Boot Up Floppy Seek

Seek disk drives during boot up. Disabled speeds boot-up.

The Choices: Enabled(default), Disabled.

Boot Up NumLock Status

Select power on state for Numlock.

On (default) Numpad is number keys.

Off Numpad is arrow keys.

Typematic Rate Setting

- | | |
|---------------------------|--|
| Enabled | Enabled this option to adjust the keystroke repeat rate. |
| Disabled (default) | Disabled. |

Typematic Rate (Char/Sec)

Range between 6(**default**) and 30 characters per second.
This option controls the speed of repeating keystrokes.

Typematic Delay (Msec)

This option sets the time interval for displaying the first and the second characters.

The Choices: 250(default), 500, 750, 1000.

Security Option

This category allows you to limit access to the system and Setup, or just to Setup.

- | | |
|------------------------|---|
| System | The system will not boot and access to Setup will be denied if the correct password is not entered in prompt. |
| Setup (default) | The system will boot, but access to Setup will be denied if the correct password is not entered in prompt. |

OS Select For DRAM

Select the operating system that is running with greater than 64MB of RAM on the system.

The Choices: Non-OS2(default), OS2.

Video BIOS Shadow

Determines whether video BIOS will be copied to RAM for faster execution.

- | | |
|--------------------------|---------------------------|
| Enabled (default) | Optional ROM is enabled. |
| Disabled | Optional ROM is disabled. |

C8000-CFFFF Shadow / D0000-DFFFF Shadow

Determines whether video BIOS will be copied to RAM for faster execution.

Enabled Optional ROM is Shadowed.

Disabled (default) Optional ROM is not Shadowed.

Note: For C8000-DFFFF option-ROM on PCI BIOS, BIOS will automatically enable the shadow RAM. User does not have to select the item.

Small Logo(EPA) Show

The Choices: Disabled(default), Enabled.

2.4 Advanced Chipset Features

This section allows you to configure the system based on the specific features of the installed chipset. This chipset manages bus speeds and access to system memory resources, such as DRAM and external cache. It also coordinates communications of the PCI bus. It must be stated that these items should never need to be altered. The default settings have been chosen because they provide the best operating conditions for your system. The only time you might consider making any changes would be if you discovered that data was lost while using your system.

© Figure 4. Advanced Chipset Features

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

Advanced Chipset Features

DRAM Clock / Drive Control	Press Enter	Item Help
AGP & P2P Bridge Control	Press Enter	Menu Level
CPU & PCI Bus Control	Press Enter	
Chipset Register Adjust	Press Enter	
Memory Hole	Disabled	
System BIOS Cacheable	Disabled	
Video RAM Cacheable	Disabled	
Delay Prior to Thermal	16 min	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

DRAM Clock / Drive Control

Current FSB Frequency		Item Help
Current DRAM Frequency		Menu Level
DRAM Clock	By SPD	
DRAM Timing	By SPD	
*SDRAM CAS Latency	2	
*Bank Interleave	Disabled	
*Precharge to Active(Trp)	3T	
*Active to Precharge(Tras)	6T	
*Active to CMD(Trcd)	3T	
*DRAM Burst Len	4	
DRAM Command Rate	2T	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

DRAM Clock

This item determines DRAM Clock following the CPU host clock.

The Choices: By SPD(default), 100, 133.

DRAM Timing

The DRAM timing is controlled by the DRAM Timing Registers. The Timings programmed into this register are dependent on the system design.

The Choices: By SPD(default), Manual.

SDRAM CAS Latency

2 (default) Set SDRAM latency Time to 2.
3 Set SDRAM latency Time to 3.

Bank Interleave

The Choices: Disabled(default), Enabled.

Active to Precharge

7T Set DRAM Precharge in 7.
6T (default) Set DRAM Precharge in 6.
5T Set DRAM Precharge in 5.

DRAM Command Rate

The Choices: 2T Command(default), 1T Command.

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

AGP & P2P Bridge Control

AGP Aperture Size	64M	Item Help
AGP Mode	4X	Menu Level
AGP Driving Control	Auto	
AGP Driving Value	DA	
AGP Fast Write	Disabled	
AGP Master 1WS Write	Disabled	
AGP Master 1WS Read	Disabled	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

AGP Aperture Size

Select the size of the Accelerated Graphic Port(AGP) aperture. The aperture is a portion of the PCI memory address range dedicated for graphics memory address space. Host cycle that hit the aperture range are forwarded to the AGP without any translation.

The Choices: 64M(default), 32M, 16M, 8M, 4M, 128M.

AGP Mode

The Choices: 4X(default), 2X, 1X.

AGP Driving Control

By choosing “Auto” the system BIOS will enable the AGP output Buffer Drive strength that were defined by AGP Card. By choosing “Manual”, it allows user to set AGP output Buffer Drive strength by manual.

The Choices: Auto(default), Manual.

AGP Fast Write

The Choices: Disabled(default), Enabled.

AGP Master 1WS Write

When Enabled, write data to the AGP (Accelerated Graphic Port) that will be executed with one wait states.

The Choices: Disabled(default), Enabled.

AGP Master 1WS Read

When Enabled, read data to the AGP (Accelerated Graphic Port) that will be executed with one wait states.

The Choices: Disabled(default), Enabled.

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

CPU & PCI Bus Control

CPU to PCI Write Buffer	Enabled	Item Help
PCI Master 0 WS Write	Enabled	Menu Level
PCI Delay Transaction	Disabled	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

CPU to PCI Write Buffer

When this field is Enabled, write from the CPU to the PCI bus are buffered, to compensate for the speed differences between the CPU and the PCI bus. When Disabled, the are not buffered and the CPU must wait until the write is complete before starting another write cycle.

The Choices: Enabled(default), Disabled.

PCI Master 0 WS Write

When this field is Enabled, write data to the PCI bus are executed with zero wait states.

The Choices: Enabled(default), Disabled.

PCI Delay Transaction

The Choices: Disabled(default), Enabled.

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

Chipset Register Adjust

DRAM Driv-0	Auto	Item Help
D/0 Value	BA	Menu Level
DRAM Driv-1	Auto	
D/1 Value	0B	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

DRAM Driv-0

The Choices: Auto(default), Manual.

DRAM Driv-1

The Choices: Auto(default), Manual.

Memory Hole

In order to improve performance, certain space in memory can be reserved for ISA cards. This memory must be mapped into the memory's space below 16MB.

The Choices: Disabled(default), 15M-16M.

System BIOS Cacheable

When enabled, the access to the system BIOS ROM address at F0000H-FFFFFFH is cached.

The Choices: Disabled(default), Enabled.

Video RAM Cacheable

Enabled Enabled Video RAM Cacheable.

Disabled (default) Disabled Video RAM Cacheable.

Delay Prior to Thermal

The Choices: 16 min(default), 4min, 8min, 32min.

2.5 Integrated Peripherals

© Figure 5. Integrated Peripherals

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

Integrated Peripherals

VIA Onchip IDE Device	Press Enter	Item Help
VIA Onchip PCI Device	Press Enter	Menu Level
Super IO Device	Press Enter	
Init Display First	AGP	
Onchip USB Connector	All Enabled	
USB Keyboard Support	Disabled	
USB Mouse Support	Disabled	
IDE HDD Block Mode	Enabled	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

VIA Onchip IDE Device

On-Chip IDE Channel 0	Enabled	Item Help
On-Chip IDE Channel 1	Enabled	Menu Level
IDE Prefetch Mode	Enabled	
Primary Master PIO	Auto	
Primary Slave PIO	Auto	
Secondary Master PIO	Auto	
Secondary Slave PIO	Auto	
Primary Master UDMA	Auto	
Primary Slave UDMA	Auto	
Secondary Master UDMA	Auto	
Secondary Slave UDMA	Auto	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

On-Chip IDE Channel 0

Enabled (default)

Enabled onboard 1st channel IDE port.

Disabled

Disabled onboard 1st channel IDE port.

On-Chip IDE Channel 1

Enabled (default)

Enabled onboard 2nd channel IDE port.

Disabled

Disabled onboard 2nd channel IDE port.

IDE Prefetch Mode

The onboard IDE drive interface supports IDE prefetching, for faster drive access. If you install a primary and or secondary add-in IDE interface, set this field to Disabled if the interface does not support prefetching.

The Choices: Enabled(default), Disabled.

Primary Master PIO(for onboard IDE 1st channel)

Auto (default) BIOS will automatically detect the IDE HDD Accessing mode.

Mode 0~4 Manually set the IDE Accessing mode.

Primary Slave PIO(for onboard IDE 2nd channel)

Auto (default) BIOS will automatically detect the IDE HDD Accessing mode.

Mode 0~4 Manually set the IDE Accessing mode.

Secondary Master PIO(for onboard IDE 1st channel)

Auto (default) BIOS will automatically detect the IDE HDD Accessing mode.

Mode 0~4 Manually set the IDE Accessing mode.

Secondary Slave PIO(for onboard IDE 2nd channel)

Auto (default) BIOS will automatically detect the IDE HDD Accessing mode.

Mode 0~4 Manually set the IDE Accessing mode.

Primary Master UDMA

Auto (default) BIOS will automatically detect the IDE HDD Accessing mode.

Disabled Disabled.

Primary Slave UDMA

Auto (default)	BIOS will automatically detect the IDE HDD Accessing mode.
Disabled	Disabled.

Secondary Master UDMA

Auto (default)	BIOS will automatically detect the IDE HDD Accessing mode.
Disabled	Disabled.

Secondary Slave UDMA

Auto (default)	BIOS will automatically detect the IDE HDD Accessing mode.
Disabled	Disabled.

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software
VIA Onchip PCI Device

VIA-3058 AC97 Audio	Auto	Item Help
VIA-3068 AC97 Modem	Auto	
VIA-3043 Onchip LAN	Enabled	Menu Level
OnChip LAN Boot ROM	Disabled	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
F1:General Help F5:Previous Values F6:Fail-Safe Defaults
F7:Optimized Defaults

VIA-3058 AC97 Audio

The default setting of this item utilizes an onboard sound chip for audio output. There is no need to buy and insert a sound card. If a sound card is installed, disable this item.

The Choices: Auto(default), Disabled

VIA-3068 AC97 Modem

The item allows you to control the onboard MC97 Modem controller.

The Choices: Auto(default), Disabled.

VIA-3043 Onchip LAN

The Choices: Enabled(default), Disabled.

OnChip LAN Boot ROM

The Choices: Disabled(default), Enabled.

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

Super IO Device

Onboard FDC Controller	Enabled	Item Help
Onboard Serial Port 1	3F8/IRQ4	Menu Level
Onboard Serial Port 2	2F8/IRQ3	
UART Mode Select	Normal	
RxD,TxD Active	Hi,Lo	
IR Transmission Delay	Enabled	
UR2 Duplex Mode	Half	
Use IR Pins	IR/Rx2Tx2	
Onboard Parallel Port	278/IRQ5	
Parallel Port Mode	SPP	
EPP Mode Type	EPP1.7	
ECP Mode Use DMA	3	
Game Port Address	201	
Midi Port Address	330	
Midi Port IRQ	10	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

Onboard FDC Controller

Enabled (default)

Enabled onboard FDC Controller.

Disabled

Disabled onboard FDC Controller.

Onboard Serial Port1

Select an address and corresponding interrupt for the first and second serial ports.

The Choices: 3F8/IRQ4(default), Auto, (2F8/IRQ3), (3E8/IRQ4), (2E8/IRQ3), Disabled.

Onboard Serial Port 2

Auto

BIOS will automatically setup the Serial Port 2 address.

3F8/IRQ4

Enabled onboard Serial Port 2 and address is 3F8.

2F8/IRQ3 (default)

Enabled onboard Serial Port 2 and address is 2F8.

3E8/IRQ4	Enabled onboard Serial Port2 and address is 3E8.
2E8/IRQ3	Enabled onboard Serial Port2 and address is 2E8.
Disabled	Disabled.

UART Mode Select

This item allows you to select which Infra Red(IR) function of the onboard I/O chip you wish to use.

The Choices: Normal(default), IrDA, SCR, ASKIR.

UR2 Duplex Mode

This item allows you to select which Infra Red(IR) function of the onboard I/O chip you wish to use.

The Choices: Half(default), Full.

Onboard Parallel Port

This item allows you to select the I/O address with which to access the onboard parallel port controller.

Disabled.

378/IRQ7.

278/IRQ5. (default)

3BC/IRQ7.

Parallel Port Mode

SPP (default) Using Parallel port as Standard Parallel Port.

EPP Using Parallel port as Enhanced Parallel Port.

ECP Using Parallel port as Extended Capabilities Port.

ECP/EPP Using Parallel port as ECP/EPP mode.

Game Port Address

201 (default) Set onboard game port to 201.

209 Set onboard game port to 209.

Disabled Disabled.

Midi Port Address

300	Set Midi Port address to 300.
330 (default)	Set Midi Port address to 330.

Midi Port IRQ

10 (default)	Set Midi Port IRQ to 10.
5	Set Midi Port IRQ to 5.

Init Display First

PCI Slot	Set Init Display First to PCI Slot.
AGP (default)	Set Init Display First to onboard AGP.

Onchip USB Connector

This should be enabled if your system has a USB installed on the system board and you wish to use it. Even when so equipped, if you add a higher performance controller, you will need to disable this feature.

The Choices: **All Enabled**(default), All Disabled, 1&2 USB Port, 2&3 USB Port, 1&3 USB Port, 1 USB Port, 2 USB Port, 3 USB Port.

USB Keyboard Support

Select Enabled if your system contains a Universal Serial Bus(USB) controller and you have a USB keyboard.

The Choices: **Disabled**(default), Enabled.

USB Mouse Support

Select Enabled if your system contains a Universal Serial Bus(USB) controller and you have a USB mouse.

The Choices: **Disabled**(default), Enabled.

IDE HDD Block Mode

Enabled (default)	Enabled.
Disabled	Disabled.

2.6 Power Management Setup

The Power Management Setup allows you to configure your system to most effectively save energy while operating in a manner consistent with your own style of computer use.

© Figure 6. Power Management Setup

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

Power Management Setup

ACPI Function	Enabled	Item Help
ACPI Suspend Type	S1(POS)	
Power Management Option	User Define	Menu Level
HDD Power Down	Disabled	
Suspend Mode	Disabled	
Video Off Option	Suspend->Off	
Video Off Method	V/H SYNC+Blank	
Modem Use IRQ	3	
Soft-Off by PWRBTN	Instant-Off	
PWRON After PWR-Fail	Off	
IRQ / Event Activity Detect	Press Enter	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

ACPI Function

This item display status of the Advanced Configuration and Power Management (ACPI).

ACPI Suspend Type

The item allows you to select the suspend type under ACPI operating system.

S1(POS) (default) Power on Suspend.

S3(STR) Suspend to RAM.

Power Management Option

This option allows you to set each mode individually. When not disabled, each of the ranges are from 1 min. to 1 hr. except for HDD Power Down which ranges from 1 min. to 15 min. and disable.

The Choices: **User Define** (default), Min Saving, Max Saving.

HDD Power Down

By default, this is “Disabled”, meaning that no matter the mode of the rest of the system, the hard drive will remain ready. Otherwise, you have a range of choices from 1 to 15 minutes or Suspend. This means that you can select to have your hard disk drive be turned off after a selected number of minutes or when the rest of the system goes into a suspend mode.

The Choices: Disabled(default).

Suspend Mode

The **Suspend Mode** fields set the Period of time after each of these modes activates. At Max Saving, these modes activate sequentially (in the given order) after one minute; at Min Saving after one hour.

The Choices: Disabled(default).

Video Off Option

This field determines when to activate the video off feature for monitor power management.

The Choices: Suspend->off(default), Always on.

Video Off Method

This determines the manner in which the monitor is blanked.

- | | |
|------------------------------------|--|
| V/H SYNC+Blank
(default) | This selection will cause the system to turn off the vertical and horizontal synchronization ports and write blanks to the video buffer. |
| Blank Screen | This option only writes blanks to the video buffer. |
| DPMS Support | Initial display power management signaling. |

Modem Use IRQ

This determines the IRQ, which can be applied in Modem use.

3(default)

4/5/7/9/10/11/NA

Soft-Off by PWRBTN

Pressing the power button for more than 4 seconds forces the system to enter the Soft-Off state when the system has “hung”.

The Choices: Instant-Off(default), Delay 4 Sec.

PWRON After PWR-Fail

This option will determine how the system will power on after a power failure.

The Choices: Off(default), On, Former-Sts.

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

IRQ / Event Activity Detect

VGA	OFF	Item Help
LPT & COM	LPT/COM	
HDD & FDD	ON	Menu Level
PCI Master	OFF	
PowerOn by PCI Card	Disabled	
Modem Ring Resume	Disabled	
RTC Alarm Resume	Disabled	
Date (of Month)	0	
Resume Time (hh:mm:ss)	0 0 0	
IRQs Activity Monitoring	Press Enter	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

IRQ / Event Activity Monitoring

If you highlight the “Press Enter” next to the “Wake Up Events” label and then press the enter key, it will take you to a submenu with the following options:

VGA

When set to On, any event occurring at a VGA port will awaken a system which has been powered down.

LPT & COM

When set to On, any event occurring at a COM(serial) / LPT (printer) port will awaken a system which has been powered down.

HDD & FDD

When set to On(default), any event occurring at a hard or floppy drive will awaken a system which has been powered down.

PCI Master

When set to On, any event occurring at a PCI port will awaken a system which has been powered down.

Modem Ring Resume

To use this function, you need a LAN add-on card which supports power on function. It should also support the wake-up on LAN jump. **The Choices: Disabled**(default).

RTC Alarm Resume

When “Enabled”, you can set the date and time at which the RTC (real-time clock) alarm awakens the system from Suspend mode.

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

IRQs Activity Monitoring

Primary INTR	ON	Item Help
IRQ 3 (COM2)	Disabled	Menu Level
IRQ 4 (COM1)	Enabled	
IRQ 5 (LPT2)	Enabled	
IRQ 6 (Flippy Disk)	Enabled	
IRQ 7 (LPT1)	Enabled	
IRQ 8 (RTC Alarm)	Disabled	
IRQ 9 (IRQ2 Redir)	Disabled	
IRQ 10 (Reserved)	Disabled	
IRQ 11 (Reserved)	Disabled	
IRQ 12 (PS2/Mouse)	Enabled	
IRQ 13 (Coprocessor)	Enabled	
IRQ 14 (Hard Disk)	Enabled	
IRQ 15 (Reserved)	Disabled	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

IRQs Activity Monitoring

When set to On(default), any event occurring at Primary INTR will awaken a system which has been powered down.

The following is a list of IRQ, Interrupt ReQuests, which can be exempted much as the COM ports and LPT ports above can. When an I/O device wants to gain the attention of the operating system, it signals this by causing an IRQ to occur. When the operating system is ready to respond to the request, it interrupts itself and performs the service. As above, the choices are On and Off. Off is the default. When set On, activity will neither prevent the system from going into a power management mode nor awaken it.

IRQ3	(COM1)
IRQ4	(COM2)
IRQ5	(LPT2)
IRQ6	(Floppy Disk)
IRQ7	(LPT1)
IRQ8	(RTC Alarm)
IRQ9	(IRQ2 Redir)
IRQ10	(Reserved)
IRQ11	(Reserved)
IRQ12	(PS/2 Mouse)
IRQ13	(Coprocessor)
IRQ14	(Hard Disk)
IRQ15	(Reserved)

2.7 PnP/PCI Configurations

This section describes configuring the PCI bus system. PCI or Personal Computer Interconnect, is a system which allows I/O devices to operate at speeds nearing the speed of the CPU itself uses when communicating with its own special components. This section covers some very technical items and it is strongly recommended that only experienced users should make any changes to the default settings.

© Figure 7. PnP/PCI Configurations

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

PnP/PCI Configurations

PNP OS Installed	No	Item Help
Reset Configuration Data	Disabled	Menu Level
Resources Controlled By IRQ Resources	Auto(ESCD) Press Enter	Select Yes if you are using a Plug and Play capable operating system select No if you need the BIOS to configure non- boot devices
PCI/VGA Palette Snoop	Disabled	
Assign IRQ For VGA	Enabled	
Assign IRQ For USB	Enabled	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

PNP OS Installed

When set to YES, BIOS will only initialize the PnP cards used for booting (VGA, IDE, SCSI). The rest of the cards will be initialized by the PnP operating system like Windows 95. When set to No, BIOS will initialize all the PnP cards. Therefore for non-PnP operating systems (DOS, Netware), this option must be set to No.

Reset Configuration Data

The system BIOS supports the PnP feature so the system needs to record which resource is assigned and proceeds resources from conflict. Every peripheral device has a node, which is called ESCD. This node records which resources are assigned to it. The system needs to record and update ESCD to the memory locations. These locations (4K) are reserved at the system BIOS.

If Disabled (Default) is chosen, the system's ESCD will update only when the new configuration varies from the last one. If Enabled is chosen, the system is forced to update ESCDs and then is automatically set to the "Disabled" mode.

IRQ3	assigned to:PCI/ISA PnP
IRQ4	assigned to:PCI/ISA PnP
IRQ5	assigned to:PCI/ISA PnP
IRQ6	assigned to:PCI/ISA PnP
IRQ7	assigned to:PCI/ISA PnP
IRQ8	assigned to:PCI/ISA PnP
IRQ9	assigned to:PCI/ISA PnP
IRQ10	assigned to:PCI/ISA PnP
IRQ11	assigned to:PCI/ISA PnP
IRQ12	assigned to:PCI/ISA PnP
IRQ13	assigned to:PCI/ISA PnP
IRQ14	assigned to:PCI/ISA PnP
IRQ15	assigned to:PCI/ISA PnP
DMA-0	assigned to:PCI/ISA PnP
DMA-1	assigned to:PCI/ISA PnP
DMA-2	assigned to:PCI/ISA PnP
DMA-3	assigned to:PCI/ISA PnP
DMA-4	assigned to:PCI/ISA PnP
DMA-5	assigned to:PCI/ISA PnP
DMA-6	assigned to:PCI/ISA PnP
DMA-7	assigned to:PCI/ISA PnP

The above settings will be shown on the screen only if “Manual” is chosen for the resources controlled by function.

Legacy is the term which signifies that a resource is assigned to the ISA Bus and provides for non-PnP ISA add-on cards. PCI/ISA PnP signifies that a resource is assigned to the PCI Bus or provides for ISA PnP add-on cards and peripherals.

Resources Controlled By

By Choosing “Auto” (default), the system BIOS will detect the system resources and automatically assign the relative IRQ and DMA channel for each peripheral. By Choosing “Manual” the user will need to assign IRQ & DMA for add-on cards. Be sure that there are no IRQ/DMA and I/O port conflicts.

IRQ Resources

When resources are controlled manually, assign each system interrupt a type, depending on the type of device using the interrupt.

PCI / VGA Palette Snoop

Choose Disabled or Enabled. Some graphic controllers which are not VGA compatible take the output from a VGA controller and map it to their display as a way to provide boot information and VGA compatibility.

However, the color information coming from the VGA controller is drawn from the palette table inside the VGA controller to generate the proper colors, and the graphic controller needs to know what is in the palette of the VGA controller. To do this, the non-VGA graphic controller watches for the write access to the VGA palette and registers the snoop data. In PCI based systems, the Write Access to the palette will not show up on the ISA bus if the PCI VGA controller responds to the Write.

In this case, the PCI VGA controller should not respond to the Write, it should only snoop the data and permit the access to be forwarded to the ISA bus. The non-VGA ISA graphic controller can then snoop the data on the ISA bus. Unless you have the above situation, you should disable this option.

Disabled (default)	Function Disabled.
Enabled	Function Enabled.

Assign IRQ For VGA

Lets the user choose which IRQ to assign for the VGA.

Assign IRQ For USB

Lets the user choose which IRQ to assign for the USB.

2.8 PC Health Status

© Figure 8. PC Health Status

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

PC Health Status

CPU Warning Temperature	Disabled	Item Help
Current System Temp.		Menu Level
Current CPU Temperature		
Current CPU Fan Speed		
Current System Fan Speed		
Vcore		
+3.3V		
+5V		
+12V		
-12V		
-5V		
VBAT(V)		
5VSB(V)		

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

Current Voltage(V) Vcore +12V / -12V / +5V / +3.3V / 5VSB / VBAT

Detect system's voltage status automatically.

Current CPU / System Temperature(°C/°F)

This field displays the current CPU temperature,if your computer contains a monitoring system.

Current CPU Fan / System Fan Speed

These field displays the current speed of up to System Fans,if your computer contains a monitoring system.

CPU Warning Temperature(°C)

Disabled (default)	Disabled.
50°C / 122°F	Monitor CPU Temp.at 50°C / 122°F.
53°C / 127°F	Monitor CPU Temp.at 53°C / 127°F.
56°C / 133°F	Monitor CPU Temp.at 56°C / 133°F.
63°C / 145°F	Monitor CPU Temp.at 63°C / 145°F.
66°C / 151°F	Monitor CPU Temp.at 66°C / 151°F.
70°C / 158°F	Monitor CPU Temp.at 70°C / 158°F.

2.9 Frequency / Voltage Control

© Figure 9. Frequency / Voltage Control

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software

Frequency / Voltage Control

CPU Vcore Select	Default	Item Help
Auto Detect DIMM / PCI CLK	Enabled	
Spread Spectrum	Disabled	
CPU Clock	100	Menu Level
CPU Ratio	X8	

←→↑↓: Move Enter:Select +/-/PU/PD:Value F10:Save ESC:Exit
 F1:General Help F5:Previous Values F6:Fail-Safe Defaults
 F7:Optimized Defaults

CPU Vcore Select

This item allows you to select voltage.

The Choices: Default, +0.025V~-+0.1V, -0.025V~-0.1V.

Auto Detect DIMM / PCI CLK

This item allows you to enable/disable auto detect DIMM / PCI CLOCK.

The Choices: Enabled(default), Disabled.

Spread Spectrum

This function is designed to EMI test only.

The Choices: Disabled(default), +/-0.25%~-+/-0.5%, -0.5%.

CPU Clock

This item allows you to select the CPU clock from 133MHz to 166MHz, 100MHz to 133MHz or 66MHz to 100MHz depending on the CPU Host Clock .

The Choices: 100(default), Min.66~Max.133.

CPU Ratio

This option will not be shown if you are using a CPU with the locked ratio.

The Choices: X8~X23.

NOTE:


Intel CPU doesn't support overclock and overvcore, we don't recommend users use these funtions for possible CPU damage.

2.10 Load Fail-Safe Defaults

When you press <Enter> on this item, you get a confirmation dialog box with a message similar to:

© Figure 10. Load Fail-Safe Defaults

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software




Pressing 'Y' loads the default values that are factory settings for optimal performance of system operations.

2.11 Load Optimized Defaults

When you press <Enter> on this item, you get a confirmation dialog box with a message similar to:

© Figure 11. Load Optimized Defaults

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software




Pressing ‘Y’ loads the default values that are factory settings for optimal performance of system operations.

2.12 Set Supervisor / User Password

© Figure 12. Set Supervisor / User Password

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software



When you select this function, the following message will appear at the center of the screen to assist you in creating a password.

Enter Password

Type a password, up to eight characters, and press <Enter>. The password you type now will clear any previously entered password from CMOS memory. You will be asked to confirm the password. Type the password again and press <Enter>. You may also press <ESC> to abort the selection and not enter a password. To disable the password, just press <Enter> when you are prompted to enter a password. A message will confirm that you wish to disable the password. Once the password is disabled, the system will boot and you can enter setup freely.


Password Disabled

If you select “System” at the Security Option of BIOS Features Setup Menu, you will be prompted for the password every time when the system is rebooted, or any time when you try to enter Setup. If you select “Setup” at the Security Option of the BIOS Features Setup Menu, you will be prompted only when you try to enter Setup.

2.13 Save & Exit Setup

© Figure 13. Save & Exit Setup

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software




Typing “Y” will quit the Setup Utility and save the user setup value to RTC CMOS RAM.

Typing “N” will return to the Setup Utility.

2.14 Exit Without Saving

© Figure 14. Exit Without Saving

CMOS Setup Utility-Copyright (C) 1984-2001 Award Software



Typing “Y” will quit the Setup Utility without saving to RTC CMOS RAM.

Typing “N” will return to the Setup Utility.

3. Driver Installation

Introduction

There are motherboard drivers in CD disc. You don't need to install all of them in order to boot your system. But after you finish the hardware installation, you have to install your operating system first (such as windows 98) before you can install any drivers or utilities. Please refer to your operating system installation guide.

Note: Please follow recommended procedure to install Windows ME and Windows 98.

3.1 Auto-run Menu

You can use the auto-run menu of Bonus CD disc.
Choose the utility or driver and select model name.




3.2 Installing VIA 4 in 1 Driver


You can install the VIA 4 in 1 driver (IDE Bus master (For Windows NT use), VIA ATAPI Vendor Support Driver, VIA AGP, IRQ Routing Driver (For Windows 98 use), VIA Registry (INF) Driver) from the Bonus Pack CD disc auto-run menu.



(1)
Click
"VIA 4in1" Item.



(2)
Click
"Setup" Item.



(3)
Click "Next".


Note: Installing this Bus Master IDE driver may cause Suspend to Hard Drive failure.

3.3 Installing Audio Driver


This motherboard comes with an AC97 CODEC and the sound controller is in VIA South Bridge chipset. This item install the VIA Audio for Microsoft Windows 9X/98SE/ME/NT4.0/2000/XP.



(1)
Click
"VIA Audio" Item.



(2)
Click
"Via8233" Item.




(3)
Click "Setup".

Note:


For Win NT, Win 2000, WinXP
,Win 9X/SE/ME system.

3.4 Installing LAN Driver


When your mainboard comes with the VIA PCI 10/100Mb Fast Ethernet Adapter, you must install the VIA® LAN driver to support the LAN function. In some operating systems like Windows 98, Windows 2000, Windows NT the provided CD will auto-run when you insert the CD disk into the CD-ROM drive.



(1)
Click
"System" Item.




(2)
Select
"Other Devices"
then Click
"PCI Ethernet
Controller" Item.




(3)
Select
"Driver"
then Click
"Update Driver" Item.




(4)
Click
"Next" Item.




(5)
Click
"Next" Item.



(6)
Selection your system environment follow path :
\\MB\LAN_driver\VT6103
then
Click "Next" Item.



(7)
Click "Next" Item.



(8)
Click "Finish" Item.

4PX266A System Compatibility Test Report

**** Note:**
 This test report is for your reference, we would like to suggest you to use these devices that we had approved.

A. CPU & Memory Compatibility Test Pass

CPU MEMORY	Pentium 4 1.5GHz	Pentium 4 1.7GHz	Pentium 4 1.8GHz
HYUNDAI	256MBX1	256MBX2	256MBX1
HY5DU28822T-H(116A)	D1 PASS	D2,3 PASS	D3 PASS
NANYA	512MBX1	512MBX2	512MBX2
NT5DS32M8AT-7K(0046)	D3 PASS	D1,2 PASS	D2,3 PASS
HYUNDAI	128MBX2	128MBX1	128MBX1
HY5DU28822T-H(115A)	D1,3 PASS	D2 PASS	D1 PASS
SAMSUNG	256MBX2	256MBX1	256MBX2
K4H280838B-TCB0(112)	D2,3 PASS	D1 PASS	D1,3 PASS

CPU MEMORY	Pentium 4 1.5GHz	Pentium 4 1.7GHz	Pentium 4 1.8GHz
NANYA	128MBX2	128MBX1	128MBX2
NT5DS16M8AT-7KS	D2,3 PASS	D1 PASS	D1,2 PASS
NANYA	256MBX1	256MBX2	256MBX1
NT5DS16M8AT-7KS	D2 PASS	D1,2 PASS	D3 PASS
SAMSUNG	256MBX2	256MBX1	256MBX2
K4H280838B-TCB0(106)	D1,2 PASS	D3 PASS	D2,3 PASS
NANYA	128MBX1	128MBX2	128MBX1
NT5DS16M8AT-7K(0049)	D3 PASS	D2,3 PASS	D1 PASS

CPU MEMORY	Pentium 4 1.5GHz	Pentium 4 1.7GHz	Pentium 4 1.8GHz
SAMSUNG	256MBX2	256MBX2	256MBX1
K4H280838B-TCB0(106)	D1,2 PASS	D2,3 PASS	D2 PASS
NANYA	256MBX1	256MBX1	256MBX2
NT5DS16M8AT-7K(0101)	D3 PASS	D2 PASS	D1,2 PASS
SAMSUNG	128MBX2	128MBX2	128MBX1
K4H280838B-TCB0(103)	D2,3 PASS	D1,3 PASS	D3 PASS
NANYA	128MBX1	128MBX1	128MBX2
NT5DS16M8AT-7K(0049)	D1 PASS	D3 PASS	D2,3 PASS

CPU MEMORY	Pentium 4 1.5GHz	Pentium 4 1.7GHz	Pentium 4 1.8GHz
SAMSUNG	128MBX2	128MBX1	128MBX1
K4H280838B-TCB0(118)	D1,2 PASS	D2 PASS	D3 PASS
SAMSUNG	128MBX1	128MBX2	128MBX2
K4H280838B-TCB0(049)	D2 PASS	D1,3 PASS	D1,2 PASS
SAMSUNG	128MBX2	128MBX1	128MBX1
K4H280838B-TCB0(118)	D2,3 PASS	D1 PASS	D2 PASS
SAMSUNG	256MBX2	256MBX1	256MBX2
K4H280838B-TCB0(118)	D1,2 PASS	D2 PASS	D2,3 PASS

4PX266A System Compatibility Test Report

B. AGP Display Compatibility Test

Win98 SE 1024 x 768 x 32 bit

AGP Model	Vendor	AGP Mode	Dirver Version	3D MARK 2001 Bench Mode	Quake III Demo 001		
					frames	seconds	fps
V7100	ASUS	4X	4.13.01.1241	2227	1346	10.8	124.7
GA-GF1280	Gigabyte	4X	4.13.01.1241	2230	1346	10.8	124.4
MS-8817	MSI	2X	4.13.01.1241	2226	1346	10.9	123.8
GeForce 2 MX	ACORP	4X	4.13.01.1241	1238	1346	16.8	80.3
GLADIAC	ELSA	4X	4.13.01.1241	2300	1346	10.9	123.6
MS-8806	MSI	4X	4.13.01.1241	1489	1346	19	70.7
ERAZOR X-A32	ELSA	4X	4.13.01.1241	2127	1346	10.7	125.5
GeForce 2 GTS	Creative	4X	4.13.01.1241	3202	1346	9.3	145.2
G400	Matrox	4X	4.11.01.1250	1257	1346	22.2	60.6
Gladlac MX	ELSA	4X	4.13.01.1241	3541	1346	9.4	143.4

WinSE 800 x 600 x 16 bit

AGP Model	Vendor	AGP Mode	Dirver Version	3D MARK 2000 Bench Mode	Quake III Demo 001		
					frames	seconds	fps
Synergy 2000	ELSA	4X	4.13.01.1241	6480	1346	9.3	144.3
GeForce 256	ACORP	4X	4.13.01.1241	5470	1346	9.7	139.4
MS-8829	MSI	4X	4.13.01.1241	4418	1346	11.7	114.9
V7700	ASUS	4X	4.13.01.1241	8024	1346	9	150.2
V3800	ASUS	4X	4.13.01.1241	2414	1346	22	61.1
Savage 4	LEMEL	4X	4.11.01.8002	1146	1346	47	28.7
TNT 2 Vanta	ACORP	2X	4.13.01.1241	2422	1346	23.2	58.1
Synergy II-32	ELSA	4X	4.13.01.1241	4050	1346	15.3	87.9
L2300 Pro	WinFast	1X	4.12.01.2107	1868	1346	50.8	26.5
GeForce 2 MX	LEMEL	4X	4.13.01.1241	6374	1346	9.3	145.2

Win2000 1024 x 768 x 32 bit

AGP Model	Vendor	AGP Mode	Dirver Version	3D MARK 2001 Bench Mode	Quake III Demo 001		
					frames	seconds	fps
MS-8822	MSI	4X	5.13.01.1241	1351	1346	48.6	27.7
GeForce 3	WinFa	4X	5.13.01.1241	1693	1346	27.8	48.4
MS-8826	MSI	4X	5.13.01.1241	834	1346	23	58.4
GeForce 2 MX	WinFast	4X	5.13.01.1241	772	1346	48.1	28
GV-GA1280RT	Gigabyte	4X	5.13.01.1241	823	1346	27.5	48.9

Win2000 1024 x 768 x 32 bit

AGP Model	Vendor	AGP Mode	Dirver Version	3D MARK 2000 Bench Mode	Quake III Demo 001		
					frames	seconds	fps
MS-8815	MSI	4X	5.13.01.1241	1625	1346	43.4	31
RADEON	Ati	4X	5.12.2184	1240	1346	44.6	30.2
TNT 2 M64	ACORP	4X	5.13.01.1241	770	1346	55.9	24.1
V7100 Pro	ASUS	4X	5.13.01.1241	3746	1346	9.1	147.3
GeForce 2 MX MAX	WinFast	4X	5.13.01.1241	3145	1346	8.7	155.4

4PX266A System Compatibility Test Report

C. PCI/ISA Device Compatibility Test

Device Model	BUS	Vendor Model	Driver Version	Result
LAN Card	PCI	D_Link	2.52	PASS
	PCI	Intel PILA8460C3	5.40.17.0000	PASS
	PCI	Realtek 8319A	5.352.1215.1998	PASS
Sound Card	PCI	Creative Live 5.1	4.12.01.0905	PASS
	PCI	ESS Solo-1 1989S	4.12.01.7135	PASS
	PCI	YAMAHA TF-754	4.07.00.2013	PASS
VGA Card	PCI	S3 Trio64v2-DX/GX	4.10.1715	PASS
IEEE1394 Card	PCI	ACORP 1394TTO	4.10.2222	PASS
	PCI	KOUWELL KW-582V2	4.10.2222	PASS
	PCI	DOMEX DMX-5340	4.10.2222	PASS
IEEE1394 Device		Venus Series 3.5" Storage Enclosure		PASS

Win98 SE

Device Model	BUS	Vendor Model	Driver Version	Result
All PCI/ISA Device Card	PCI	PCTEL PCT789T-A	7.66-9K-03	PASS
	PCI	D_Link DFE-530TX	2.52	PASS
	PCI	ACORP BT878	Version 4.1.8.8	PASS
	PCI	Tekram DC-390U2W	3.22	PASS
	PCI	YAMAHA YF-754	4.0700.2013	PASS

Win2000

Device Model	BUS	Vendor Model	Driver Version	Result
All PCI/ISA Device Card	PCI	PCTEL PCT789T-A	7.66-9K-03	PASS
	PCI	D_Link DFE-530TX	2.52	PASS
	PCI	ACORP BT878	3.1.28.0	PASS
	PCI	Tekram DC-390U2W	3.22	PASS
	PCI	YAMAHA YF-754	5.00.2175.1	PASS

D. Other Peripherals Compatibility Test

Device Model	Vendor Model	Result
USB Mouse	DEXIN MODEL:A3U800A	Pass
	GENUINE	Pass
USB Keyboard	Microsoft Optical USB Mouse	Pass
	台園 7932M	Pass
	GENUINE K371	Pass
USB Modem	ACORP 56K Fax MODEM	Pass
USB Print	EPSON Stylus 740	Pass
USB ZIP	IOMEGA Z100	Pass
USB SCANNER	UMAX Stra 3400	Pass
USB Joystick	Microsoft SideWinder P&P Game Pad	Pass
Mouse	Microsoft PN X05-51692E	Pass
Modem	LEMEL 33.6K Modem	Pass
Print	EPSON Stylus 740	Pass
PS/2 Mouse	Microsoft PN X05-51692	Pass
PS/2 Keyboard	GENUINE FKD46AK288	Pass

4PX266A System Compatibility Test Report

E. System Reliability Test

O.S. Environment	Test Software	Version	Loop times	Result
Win98 SE	WinStone 99 Business Test	1.3	8 Hours	PASS
	3D MARK 2001 DEMO Mode Test	1.0	8 Hours	PASS
Win ME	Quake III DEMO Mode Test	1.0	8 Hours	PASS
Win NT 4.0	WinStone 99 All Test	1.3	8 Hours	PASS
	HCT System stress Test	9.5	8 Hours	
Win 2000	Content Creation Winstone 2001	1.0	8 Hours	PASS
	SysMark 2000	1.0	1 Time	PASS