

# Addendum

## P5BV3+/e

### Rev. AD0+

## Processors

- New Supported Processors

The following has been added to the list of processors supported by the system board.

Processor	SW1: 1-6	Processor	SW1: 1-6
M II-200 - 66MHz - 2.5x		M II-380 - 100MHz - 3x	
M II-266 - 66MHz - 3x		WinChip2 -233 - 66MHz - 3.5x	
M II-333 - 66MHz - 4x		K6-2/300 - 66MHz - 4.5x	
M II-333 - 75MHz - 3.5x		K6-2/450 - 100MHz - 4.5x	
M II-366 - 83MHz - 3.5x		K6-III/400 - 100MHz - 4x	
M II-366 - 100MHz - 2.5x			

- Correction

The Cyrix M II-350 processors are not available, therefore information relevant to this processor will be removed in the future version of the manual.

The external system bus clock and frequency ratio of M II-400, WinChip2-266 and WinChip2-300 processors are incorrect; therefore the DIP switch settings for these processors have been changed.

Please refer to the table on the next page for the updated settings.

IDT Processors	SW1: 1-6	IDT Processors	SW1: 1-6
WinChip2-266 - 100MHz - 2.33x		WinChip2-300 - 100MHz - 2.5x	
M II-400 - 95MHz - 3.5x			

## **BIOS**

The system board comes standard with 1MB flash memory. An optional 2MB flash memory, which includes the SDMS function, will be provided.

## **Cache Memory**

The system board supports pipeline burst, direct map write-through cache, not write-back cache.